





Technische Specificaties				
Model	IT 1500	IT 2000	IT 2500	IT 3000
Inhoud (ltr)	1550	1800	2550	2800
Gewicht (kg)	398	426	576	600
Werkdruk (bar)	8	8	8	8
Max. temperatuur (°C)	85	85	85	85
Anodes	3	3	3	3

Afmetingen				
Model	IT 1500	IT 2000	IT 2500	IT 3000
Totale hoogte (mm)	1880	2068	1939	2068
Diameter (mm)	1200	1200	1500	1500
① Koud water aansluiting	R 2"	R 2"	R 2"	R 2"
② Warm water aansluiting	R 2"	R 2"	R 2"	R 2"
③ Aansl. aanvoer warmtewisselaar	Rp 1¼"	Rp 1¼"	Rp 1¼"	Rp 1¼"
④ Aansl. afvoer warmtewisselaar	Rp 1¼"	Rp 1¼"	Rp 1¼"	Rp 1¼"
⑦ Circulatie aansluiting	Rp 1¼"	Rp 1¼"	Rp 1¼"	Rp 1¼"
⑧ Aansluiting bodem temp. sensor	Rp ¾"	Rp ¾"	Rp ¾"	Rp ¾"
⑩ Magnesium anode aansluiting	Rp ¾"	Rp ¾"	Rp ¾"	Rp ¾"
⑪ Aansluiting T&P	Rp 1"	Rp 1"	Rp 1"	Rp 1"
⑫ Aansluiting top temp. sensor	Rp ¾"	Rp ¾"	Rp ¾"	Rp ¾"



Spécifications Technique				
Modèle	IT 1500	IT 2000	IT 2500	IT 3000
Capacité (ltr)	1550	1800	2550	2800
Poids (kg)	398	426	576	600
Pression de service (bar)	8	8	8	8
Température max. (°C)	85	85	85	85
Anodes	3	3	3	3

Dimensions				
Modèle	IT 1500	IT 2000	IT 2500	IT 3000
Hauteur totale (mm)	1880	2068	1939	2068
Diamètre (mm)	1200	1200	1500	1500
① Eau froide	R 2"	R 2"	R 2"	R 2"
② Eau chaude	R 2"	R 2"	R 2"	R 2"
③ Entrée eau chaude	Rp 1¼"	Rp 1¼"	Rp 1¼"	Rp 1¼"
④ Sortie eau chaude	Rp 1¼"	Rp 1¼"	Rp 1¼"	Rp 1¼"
⑦ Circulation	Rp 1¼"	Rp 1¼"	Rp 1¼"	Rp 1¼"
⑧ Raccordement de sonde de température inférieure	Rp ¾"	Rp ¾"	Rp ¾"	Rp ¾"
⑩ Anode de protection magnésium	Rp ¾"	Rp ¾"	Rp ¾"	Rp ¾"
⑪ Raccordement T&P	Rp 1"	Rp 1"	Rp 1"	Rp 1"
⑫ Raccordement de sonde de température supérieure	Rp ¾"	Rp ¾"	Rp ¾"	Rp ¾"



Technical Specifications				
Model	IT 1500	IT 2000	IT 2500	IT 3000
Contents (ltr)	1550	1800	2550	2800
Weight (kg)	398	426	576	600
Working pressure (bar)	8	8	8	8
Temperature max. (°C)	85	85	85	85
Anodes	3	3	3	3

Dimensions				
Model	IT 1500	IT 2000	IT 2500	IT 3000
Total height (mm)	1880	2068	1939	2068
Diameter (mm)	1200	1200	1500	1500
① Cold water	R 2"	R 2"	R 2"	R 2"
② Hot water	R 2"	R 2"	R 2"	R 2"
③ Central heating entry	Rp 1¼"	Rp 1¼"	Rp 1¼"	Rp 1¼"
④ Central heating exit	Rp 1¼"	Rp 1¼"	Rp 1¼"	Rp 1¼"
⑦ Circulation	Rp 1¼"	Rp 1¼"	Rp 1¼"	Rp 1¼"
⑧ Connection bottom temp. sensor	Rp ¾"	Rp ¾"	Rp ¾"	Rp ¾"
⑩ Magnesium anode	Rp ¾"	Rp ¾"	Rp ¾"	Rp ¾"
⑪ Connection T&P	Rp 1"	Rp 1"	Rp 1"	Rp 1"
⑫ Connection top temp. sensor	Rp ¾"	Rp ¾"	Rp ¾"	Rp ¾"