





Technische Specificaties				
Model	ST 1500	ST 2000	ST 2500	ST 3000
Inhoud (ltr)	1550	1880	2500	2820
Gewicht (kg)	324	350	483	520
Werkdruk (bar)	8	8	8	8
Max. temperatuur (°C)	95	95	95	95
Anodes	3	3	3	3

Afmetingen				
Model	ST 1500	ST 2000	ST 2500	ST 3000
Totale hoogte (mm)	1930	2118	2000	2128
Diameter (mm)	1100	1100	1400	1400
① Koud water aansluiting	R 2"	R 2"	R 2"	R 2"
② Warm water aansluiting	R 2"	R 2"	R 2"	R 2"
⑦ Circulatie aansluiting	Rp 1 1/4"	Rp 1 1/4"	Rp 1 1/4"	Rp 1 1/4"
⑦a Power anode aansluiting	Rp 3/4"	Rp 3/4"	Rp 3/4"	Rp 3/4"
⑦b Dompelbuis aansluiting	Rp 3/4"	Rp 3/4"	Rp 3/4"	Rp 3/4"
⑧ Magnesium anode aansluiting	Rp 3/4"	Rp 3/4"	Rp 3/4"	Rp 3/4"
⑪ Aansluiting	R 2"	R 2"	R 2"	R 2"
⑫ Aansluiting	R 2"	R 2"	R 2"	R 2"
⑬ Temperatuur sensor	Rp 1/4"	Rp 1/4"	Rp 1/4"	Rp 1/4"
⑭ Aansluiting	R 2"	R 2"	R 2"	R 2"



Spécifications Technique				
Modèle	ST 1500	ST 2000	ST 2500	ST 3000
Capacité (litr)	1550	1880	2500	2820
Poids (kg)	324	350	483	520
Pression de service (bar)	8	8	8	8
Température max. (°C)	95	95	95	95
Anodes	3	3	3	3

Dimensions				
Modèle	ST 1500	ST 2000	ST 2500	ST 3000
Hauteur totale (mm)	1930	2118	2000	2128
Diamètre (mm)	1100	1100	1400	1400
① Eau froide	R 2"	R 2"	R 2"	R 2"
② Eau chaude	R 2"	R 2"	R 2"	R 2"
⑦ Circulation	Rp 1 1/4"	Rp 1 1/4"	Rp 1 1/4"	Rp 1 1/4"
⑦a Raccordement de power anode	Rp 3/4"	Rp 3/4"	Rp 3/4"	Rp 3/4"
⑦b Raccordement de doigt de gant	Rp 3/4"	Rp 3/4"	Rp 3/4"	Rp 3/4"
⑧ Anode de protection magnésium	Rp 3/4"	Rp 3/4"	Rp 3/4"	Rp 3/4"
⑪ Raccordement	R 2"	R 2"	R 2"	R 2"
⑫ Raccordement	R 2"	R 2"	R 2"	R 2"
⑬ Capteur de température	Rp 1/4"	Rp 1/4"	Rp 1/4"	Rp 1/4"
⑭ Raccordement	R 2"	R 2"	R 2"	R 2"



Technical Specifications				
Model	ST 1500	ST 2000	ST 2500	ST 3000
Contents (ltr)	1550	1880	2500	2820
Weight (kg)	324	350	483	520
Working pressure (bar)	8	8	8	8
Temperature max. (°C)	95	95	95	95
Anodes	3	3	3	3

Dimensions				
Model	ST 1500	ST 2000	ST 2500	ST 3000
Total height (mm)	1930	2118	2000	2128
Diameter (mm)	1100	1100	1400	1400
① Cold water	R 2"	R 2"	R 2"	R 2"
② Hot water	R 2"	R 2"	R 2"	R 2"
⑦ Circulation	Rp 1 1/4"	Rp 1 1/4"	Rp 1 1/4"	Rp 1 1/4"
⑦a Power anode connection	Rp 3/4"	Rp 3/4"	Rp 3/4"	Rp 3/4"
⑦b Immersion well connection	Rp 3/4"	Rp 3/4"	Rp 3/4"	Rp 3/4"
⑧ Magnesium anode	Rp 3/4"	Rp 3/4"	Rp 3/4"	Rp 3/4"
⑪ Connection	R 2"	R 2"	R 2"	R 2"
⑫ Connection	R 2"	R 2"	R 2"	R 2"
⑬ Temperature sensor	Rp 1/4"	Rp 1/4"	Rp 1/4"	Rp 1/4"
⑭ Connection	R 2"	R 2"	R 2"	R 2"